

The clever way to convert

Compact 2 is the advanced die-cutting and flexo solution, completed with a fully automated flexo printing station with cold foil, spot varnish, spot colours, cold/warm lamination, cast and cure, and multi-layer capabilities. A perfect all-round choice for enhancing and finishing of digital and conventional printed labels.



Compact 2 - 14"

Standard features included:

- Semi-rotary (65 m/min) die-cut
- Full rotary (100 m/min) die-cut
- 1x Servo-driven unwind, max 725mm roll diameter (3"/76mm shaft)
- 1x Servo-driven rewind, max 650mm roll diameter (3"/76mm shaft)
- Integrated ultrasonic webguide
- Servo-driven waste matrix rewind with electronic tension control
- Flexographic varnish
- Spot varnish and spot colour printing (requires register system)
- Razor blade oscillating slitting system incl. 5 knives and holders
- Register system for die and flexo with auto-position eye-mark readers

Included options:

- Pneumatic splice table with two pneumatic clamps
- Lamination station for self-wound laminates including silencer arm
- Automated side register control (2D register control)
- 30" magnetic cylinder including adjustable bearing blocks and spacers
- GEW UV system
- Anilox 9cm3
- Coating roller 325mm
- Ductor roller
- Semi-rotary option for flexo
- Coldfoil/UV lamination (No coldfoil in semirotative mode)



Unit #162 TC USA*

Net price:

\$165.000

Incl. import duty and tariffs. Ex. works.

Expected delivery: Four to eight weeks.

Standard warranty incl. 12 months Nilpeter Hotline contract.

*Technology Center USA

- Electronic adjustable anvil2
- Integrated ink pump
- Ink tray for ink pump
- Additional servo driven rewind spindle 3"

Substrate specifications

Web width	100 mm - 450 mm
Substrate	Adhesive base material
Substrate thickness	Min. 90/max. 350 microns

For inquiries, please contact Nilpeter USA -
Tel. +1 513 489 4400 or US-Sales@nilpeter.com